

Series 217 Product Overview

Features:

- Low profile
- Large handle clearance in the open position
- Available in stainless steel

Applications:


- Assembly
- Checking fixtures
- Closures
- Woodworking

Also Available:


See page 8.1 for accessories

Accommodates M6 or 1/4" spindle accessory

**217-U**  
Flanged Base  
U-Bar




**217-USS**  
Flanged Base  
U-Bar, Stainless  
Steel




**217-UB**  
Straight Base  
U-Bar



**217-U-L** ⓘ  
Flanged Base  
Open Bar



**217-UB-L** ⓘ  
Straight Base  
Open Bar




Note:  
Clamps shown with included accessories.

Series 217 Technical Information

Model	Max. Holding Capacity	Clamp Bar Opening (+10°)	Handle Opening (+10°)	Weight	Accessories (Supplied)	
					Spindle Assembly	Flanged Washers
<b>217-U</b>	900 N [200 lbf]	91°	61°	0,18kg [0.40lb]	202208-M	215105
<b>217-USS</b>	1110 N [250 lbf]				202943	215105
<b>217-UB</b>	900 N [200 lbf]				202208-M	215105
<b>217-U-L</b> ⓘ		--	--			
<b>217-UB-L</b> ⓘ						

ⓘ This item is available upon request

## Series 217 Holding Capacities




Model	X	X1	X2	Y	±HC1	±HC2	±EF(X1):AF	±EF(X2):AF
<b>U</b>					[200lbf.] 900N	[80lbf.] 360N		
<b>USS</b>	[0.53] 13,5	[1.13] 28,6	[2.63] 66,8	[2.93] 74,5	[250lbf.] 1110N	[100lbf.] 440N	7:1	3:1
<b>UB/U-L/ UB-L</b>					[200lbf.] 900N	[80lbf.] 360N		

Dimensions shown "mm [inch]" ± HC = Holding Capacity, EF = Exerting Force, AF = Applied Force  
Refer to page 20.4 for additional information.

## Series 217 Standard Clamp Dimensions -U/-USS/-UB

### Series 217 Open Bar





Flanged Base  
Model  
**217-U-L**



Straight Base  
Model  
**217-UB-L**

See page 8.7 for Complete offering of Open bar accessories



See page 2.16 for dimensions not shown

### 217-U<sup>†</sup> Flanged Base U-Bar

